

# Inspection Table



**TA1**

**Suitable crops**



**TA2**

*This sorting table is intended for manual fruit sorting. For nuts, it's used to separate the good from the bad nuts. It's also used to separate the shells from the kernels after breaking. The height of the table and the speed are adjustable in order to offer you maximum working comfort.*

## TECHNICAL CHARACTERISTICS

	TA10001	TA10002	TA20001	TA20002
Length:	2 m	3 m	2 m	3 m
Width:	500 mm		500 mm	
Motorization:	Three-phase geared motor 0.18 kW 7.4 at 40 RPM		Three-phase geared motor 0.18 kW 5.6 at 30 RPM	
Chassis:	Galvanized-bolted structure in bent sheet metal			
Conveyor belt:	- Food grade PVC band with notched guide profile  - Tensioner with cast iron bearing, grease nipple and through shaft		- Food blue PU tape with smooth guide profile  - Tensioner with permanently greased sheet metal bearing and through shaft	
Rollers maintenance:	- PVC rolls diameter 115  - Return roller with fixed axis greased for life		-	
Product output:	Tilting outlet chute		Tilting outlet chute	-
Corridors:	2 waste lanes 75 mm wide height 50mm		2 waste channels 60 mm wide 8 mm high (per guide profile)	
Waste outlet:	-	-	2 side chutes with fixed waste with cover	
Feet:	Adjustable galvanized feet for height from floor to mat 720 to 1070 mm		Galvanized adjustable foot for a height from the floor to the 776 to 1076 mm	
Weight:	120 kg	120 kg	150 kg	150 kg

## OPTIONS

	TA10001	TA10002	TA20001
Width:	600 mm TA10006; 400 mm (without variator) TA10003	600 mm TA10007	600 mm TABLE CASCADE INOX TA30001
Length:	Length 4 m - Width 500 mm TA10012		2 mats of 1.30 m
Width and length:	Length 4 m - Width 800 mm TA10005		
Corridors:	1 corridor only; 2 corridors width XX		

**tel: 032 2 044 333**

**e-mail: [sales@farmarea.ge](mailto:sales@farmarea.ge)**